

FALL PROTECTIO N

Zawaya offers a comprehensive range of fully certified body harnesses and lanyards. Our stitching patterns and webbing configurations are specially designed to offer comfort, safety and durability to the end users. All the accessories are very carefully engineered and tested to offer customers dependability on the products we offer.



FREEDOM LITE MULTIPRO

- Description**
Full body harnesses with polyester webbing.
- Accreditation**
EN 361-2002
- Hazard**
• Fall

- Specification**
 - Webbing Material: High Tenacity Ploy, 44 mm
 - Breaking Strength: 24 KN
 - Metal Components: Electro deposited nickel chrome steel, deburred & polished
 - Static Strength: 15 KN for 3 min at each attachment
 - Dynamic Strength: 4 meter height donned to a test dummy weighing 100 kg at each attachment

- Weight: 1040 grams
- Size: Universal
- Applications**
 - Construction
 - Fabrication Industry
 - Facility Management
 - Oil & Gas
 - Signage Industry



FREEDOM MAX MULTIPRO

- Description**
Full body harnesses with polyester webbing.
- Accreditation**
EN 361-2002
- Hazard**
• Fall

- Specification**
 - Webbing Material: High Tenacity Ploy, 44 mm
 - Breaking Strength: 24 KN
 - Metal Components: Electro deposited nickel chrome steel, deburred & polished
 - Static Strength: 15 KN for 3 min at each attachment
 - Dynamic Strength: 4 meter height donned to a test dummy weighing 100 kg at each attachment

- Weight: 1120 grams
- Size: Universal
- Applications**
 - Construction
 - Fabrication Industry
 - Facility Management
 - Oil & Gas
 - Signage Industry



FREEDOM MAX R MULTIPRO

- Description**
Full body rescue harness.
- Accreditation**
EN 361-2002, EN 1497
- Hazard**
• Fall

- Specification**
 - Webbing Material: Polyester, 44mm
 - Breaking Strength: 25 KN
 - Metal Components: Electro deposited zinc alloy steel
 - Static Strength: 15 KN for 3 min at each attachment
 - Dynamic Strength: 4 meter height donned to a test dummy weighing 100 kg at each attachment
 - Weight: 1720 grams
 - Size: Universal

- Applications**
 - Construction
 - Fabrication Industry
 - Facility Management
 - Oil & Gas
 - Signage Industry



FREEDOM EXTREME MULTIPRO

- Description**
Full body rescue harness with work positioning belt.
- Accreditation**
EN 361-2002 & EN 358-1999
- Hazard**
• Fall

- Specification**
 - Webbing Material: High Tenacity Ployamide, 44 mm
 - Breaking Strength: 24 KN
 - Metal Components: Electro deposited nickel chrome steel, deburred & polished
 - Static Strength: 15 KN for 3 min at each attachment
 - Dynamic Strength: 4 meter height

- donned to a test dummy weighing 100 kg at each attachment
- Weight: 1720 grams
- Size: Universal
- Applications**
 - Construction
 - Fabrication Industry
 - Facility Management
 - Oil & Gas
 - Signage Industry



FREEDOM LANYARDS F1.5, 1.8, 2 MULTIPRO

- Description**
Webbing Lanyard - 30KN breaking strength.
- Accreditation**
EN 355-2002
- Hazard**
• Fall

- Specification**
 - Webbing Material: High Tenacity Ploy, 44 mm
 - Breaking Strength: 30 KN
 - Metal Components: Electro deposited nickel chrome steel, deburred & polished
 - Static Strength: 22 KN for 3 min at each attachment
 - Dynamic Strength: 4 meter height

- donned to a test dummy weighing 100 kg at each attachment
- Weight: 1700 & 1720 grams
- Sizes: Universal
- Options: 1.5m, 1.8m, 2m

- Applications**
 - Construction
 - Fabrication Industry
 - Facility Management
 - Oil & Gas
 - Signage Industry



FREEDOM LANYARDS KK1.5, KK1.8 MULTIPRO

- Description**
Webbing lanyard with 2 karabiners- 24KN breaking strength.
- Accreditation**
EN 355-2002
- Hazard**
• Fall

- Specification**
 - Webbing Material: High Tenacity Ploy, 44 mm
 - Breaking Strength: 24 K+D6N
 - Metal Components: Electro deposited nickel chrome steel, deburred & polished. Static Strength: 22 KN for 3 min at each attachment
 - Dynamic Strength: 4 meter height donned to a test dummy weighing 100 kg at each attachment

- Weight: 780, 820, 840 grams
- Sizes: Universal
- Options: 1.5m & 1.8

- Applications**
 - Construction
 - Fabrication Industry
 - Facility Management
 - Oil & Gas
 - Signage Industry



FREEDOM LANYARDS KS1.5, KS1.8, KS2 MULTIPRO

- Description**
Webbing lanyard with 1 karabiner & scaffold hook - 24KN breaking strength.
- Accreditation**
EN 355-2002
- Hazard**
• Fall

- Specification**
 - Webbing Material: High Tenacity Ploy, 44 mm
 - Breaking Strength: 24 KN
 - Metal Components: Electro deposited nickel chrome steel, deburred & polished
 - Static Strength: 22 KN for 3 min at each attachment
 - Dynamic Strength: 4 meter height donned to a test dummy weighing 100 kg at each attachment

- Weight: 1020, 1060 & 1160 grams
- Sizes: Universal
- Options: 1.5 m, 1.8m & 2m

- Applications**
 - Construction
 - Fabrication Industry
 - Facility Management
 - Oil & Gas
 - Signage Industry

